

# LED FLOODLIGHTS

## Data Sheet

### Features

- 850 Lumens - 6800 Lumens
- 5500K Cool White & 3200K Warm White
- 10W - 80W
- IP65 rating
- Aluminium Die Cast Housing
- Ideal for: Factories, Stadiums, Docks, Airports, Shopping Malls, Billboards, Buildings, Gardens, Museums and Galleries

### Specifications

- IP Rating: IP65
- Length of Pre-fitted Cable: 1.5m
- Warranty: 3 Years
- Chipset: Tiawan SB
- Frequency: 50Hz ~ 60Hz
- Power Factor: >0.98
- CRI: >75
- Life (Hours): 50,000
- Dimmable: No
- Material: Aluminium Die Cast
- PIR Detection Distance 25°: 4-6m (<25°)
- PIR Detection DiRange: 120°
- Time Delay: 5 sec ~ 10 min
- Override Function: Yes
- Certificate: >CE, Rohs



Part Number	Colour	Wattage	Lumens	Colour Temperature	PIR, Lux & Time Sensor	Voltage
LXFL10WB	Black	10W	850Lm	5500K	No	85V-265V AC
LXFL10WG	Grey	10W	850Lm	5500K	No	85V-265V AC
LXFL10WB-WW	Black	10W	850Lm	3200K	No	85V-265V AC
LXFL10WG-WW	Grey	10W	850Lm	3200K	No	85V-265V AC
LXFL10WB-PIR	Black	10W	850Lm	5500K	Yes	85V-265V AC
LXFL10WG-DC	Grey	10W	850Lm	5500K	No	10V-30V DC
LXFL20WB	Black	20W	1700Lm	5500K	No	85V-265V AC
LXFL20WG	Grey	20W	1700Lm	5500K	No	85V-265V AC
LXFL20WB-WW	Black	20W	1700Lm	3200K	No	85V-265V AC
LXFL20WG-WW	Grey	20W	1700Lm	3200K	No	85V-265V AC
LXFL20WB-PIR	Black	20W	1700Lm	5500K	Yes	85V-265V AC
LXFL30WB	Black	30W	2550Lm	5500K	No	85V-265V AC
LXFL30WG	Grey	30W	2550Lm	5500K	No	85V-265V AC
LXFL30WB-WW	Black	30W	2550Lm	3200K	No	85V-265V AC
LXFL30WG-WW	Grey	30W	2550Lm	3200K	No	85V-265V AC
LXFL30WB-PIR	Black	30W	2550Lm	5500K	Yes	85V-265V AC
LXFL50WB	Black	50W	4250Lm	5500K	No	85V-265V AC
LXFL50WG	Grey	50W	4250Lm	5500K	No	85V-265V AC
LXFL50WB-WW	Black	50W	4250Lm	3200K	No	85V-265V AC
LXFL50WG-WW	Grey	50W	4250Lm	3200K	No	85V-265V AC
LXFL50WB-PIR	Black	50W	4250Lm	5500K	Yes	85V-265V AC
LXFL80WB	Black	80W	6800Lm	5500K	No	85V-265V AC